



DATA	CODICE	REV
01/04/07	8621100	q



Mod. V64

STRAIGHT PLATFORM STAIRLIFT FOR WHEELCHAIRS

VARIABLES	V64					
L Width	830	830	830	1050	1050	1250
P Depth	650	700	770	700	770	800
H1-H1*	1710	1760	1830	1760	1830	1900*
T	1240	1240	1240	1460	1460	1660
T1-T1*	870	870	870	1070	1070	1260*
B	1310	1310	1310	1420	1420	1520
N	1500	1500	1500	1720	1720	1920
D-D**	370/400**	370/400**	370/400**	370/400**	370/400**	370/400**
E-E**	440/450**	440/450**	440/450**	440/450**	440/450**	440/450**

B	Guide rail dimensions, bottom landing	D**	Dimensions of seat plus fixed front guard
N	Machine dimensions, bottom landing	E	Dimensions with front slop
D	Dimensions with fixed front guard	E**	Dimensions of seat plus front slop

VARIABLES	V64					
	(830 650)	(830 700)	(830 770)	(1050 700)	(1050 770)	(1250 800)
A Side ramp	2550	2550	2550	2750	2750	2950
A Front ramp	1550	1550	1550	1750	1750	1950
LS Side ramp	920	970	1040	970	1040	1070
LS Fixed front ramp	1135	1185	1255	1185	1255	1290
LS Powered front ramp	955	1005	1075	1005	1075	/
C Vertical arms (rest)	2260	2310	2380	2430	2500	2590
C Horizontal arms (working)	1725	1725	1725	1840	1840	1890

TECHNICAL FEATURES	
Rated Load up to 45°	230 daN
Rated Load over 45°	200 daN
Voltage	230 V-mon.
Motor Voltage	230 V-mon.
Auxiliary voltage	24 V-cc
Power	0.75 KW
Speed	5 m/min

A	Minimum landing area
LS	Staircase width

DATA	CODICE	REV
01/04/07	8621100	9

Dimensions "A-LS-C" are referred to a regular staircase with a slope of 30°. Data are indicative, not binding. The Company reserves the right to undertake all necessary modification without prior notification.